




ARTEC
antifortunistica

FA 20 100 XX

P. 1 | 2



HS CODE

56090090

CARTON SIZE / PCS.

FA 20 100 10 : 80 x 40 x 24 cm / 10

FA 20 100 20 : 80 x 40 x 24 cm / 5

FA 20 100 30 : 80 x 40 x 24 cm / 5

FA 20 100 40 : 80 x 40 x 24 cm / 3

FA 20 100 50 : 80 x 40 x 24 cm / 3

AET N° 2777/10357-02/E03-01

Satra Technology Europe Ltd., N° 2777,

Bracetown Business Park, Clonee,





Dublin, D15YN2P, Ireland

MODULE D FI14/14003.02

SGS Fimko Oy, N°0598


Takomotie 8,

00380 HELSINKI, Finland


REF.	FA 20 100 XX
LG.  KG	10m 20 m 30 m 40 m 50 m
CE	EN 353-2:2002
MAT.	Polyamide Ø 14 – 16 mm
	---
	---
R(kN)	15 kN
+	FA 20 100 00A / FA 20 100 00B
	1.25 kg 2.50 kg 3.90 kg 5.15 kg 6.05 kg



Longueur Poids maxi utilisateur
Length Max. user weight
Longitud Peso máximo del usuario
Lunghezza Peso Max. dell'utente
Länge Höchstgewicht des Benutzers



Matière connecteur
 Material of connector
Material conector
 Materiale connettore
Material des Verbinders



Coulisseau doté d'un point fixe
 Rope grab with a fixed point lock
Corredera provista de punto fijo
 Guida a punto fisso
Gleitelement mit Festpunkt

+

À utiliser avec
 To be used with
Para usar con
 Ad essere utilizzato con
Verwendet werden soll mit